

Technical data

Art. no.	687403
Gauge	H0 / TT
PIN/Interface	6 pole
According to NEM	☒ Yes ☐ No 651
Cable	☒ Yes ☐ No
DCC	☒ Yes ☐ No
MM	☒ Yes ☐ No
Load regulation	☒ Yes ☐ No
POM	☒ Yes ☐ No
NMRA compatible	☒ Yes ☐ No
Speed steps (14, 28, 128)	☒ Yes ☐ No
Max. motor current	1.0 A
Light and function outputs – of which outside interface	6, summary current: max. 0.8 A 3
Max. decoder sum current	1.0 A
Short-circuit protection of all outputs	☒ Yes ☐ No
Dimensions	20 x 11 x 3.5 mm
RailCom®	☒ Yes ☐ No
Complies with ZIMO article	☒ Yes ☐ No MX630N
Updatable	☒ Yes ☐ No
Breaking section support	
Lenz ABC	☒ Yes ☐ No
Märklin 72441/72442	☒ Yes ☐ No
ZIMO HLU	☒ Yes ☐ No
Connection possibility for energy storage	☐ Yes ☒ No
Standard sound (Steam-, Diesel-, Electric locomotives)	☐ Yes ☒ No
Loudspeaker	☐ Yes ☒ No